



MATERIAL SAFETY DATA SHEET

Last Update: October, 2009

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Emergency Phone: CHEMTREC **800-424-9300** ANSI 2400.1 Format

This MSDS complies with 29 CFR 1910.1200 (OSHA Hazard Communication Standard) and Canadian WHMIS Regulations.

IMPORTANT: Read this MSDS before handling and disposing of this product. Pass this information on to employees, customers and users of this product.

Product Name: Butyl Tape Primer
Item Number: BP-40
Intended Use: Primer for UT-40 Universal Tape
Comparable Products: ProtectoWrap BT Primer

Company Information: STS COATINGS, INC., Inc.
347 Hwy 289
Comfort, TX 78013
Ph. 830-995-5177 fax 830-995-5705

Prepared by: Cayce Kovacs

2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Component	CAS NO.	Amount	Exposure Limit
Acetone	67-64-1	20-30%	1000 ppm PEL-TWA 500 ppm TLV-TWA 750 ppm TLV-STEL
Aliphatic Solvent Naphtha	64742-89-8	20-30%	100 ppm PEL-TWA 400 ppm TLV-TWA
Toluene	108-88-3	10-20%	200 ppm PEL-TWA 50 ppm TLV-TWA skin

Non-Hazardous Components >1%: Resins and Polymers 30-40%

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

HMIS	
Health	2
Flammability	3
Reactivity	0
Protective	
Equipment	B

This product is a water-white liquid with a ketone odor. Liquid and vapors are flammable. May cause eye and skin irritation. Inhalation of vapors or mist may cause respiratory irritation and central nervous system effects such as headache, dizziness, drowsiness, nausea and unconsciousness. Prolonged and/or repeated overexposure may cause liver, kidney, and nervous system damage.

4. FIRST AID MEASURES



EYE: First check victim for contact lenses and remove if present. Flush victim's eyes with large quantities of water for at least 15 minutes, holding the eyelids apart. Get medical attention if irritation persists.

SKIN: Remove contaminated clothing. Wash skin thoroughly with soap and water. If rash or irritation develop, get medical attention. Launder clothing before re-use. (Discard contaminated shoes)

INGESTION: If conscious, rinse mouth with water. Never give anything by mouth to an unconscious or convulsing person. **DO NOT INDUCE VOMITING.** Get immediate medical attention.

INHALATION: Immediately remove victim to fresh air. If breathing is difficult have qualified personnel administer oxygen. If breathing has stopped, administer artificial respiration. Get immediate medical attention.

5. FIRE FIGHTING MEASURES

FLASH POINT: <41°F (5°C) PMCC

FLAMMABLE LIMITS: LEL: 1.1% (toluene) UEL: 12.8% (acetone)

AUTOIGNITION TEMPERATURE: Not available

EXTINGUISHING MEDIA: Use carbon dioxide, universal foam, dry chemical or water fog. Do not use water stream. Use water to cool exposed containers and structures.

UNUSUAL FIRE OR EXPLOSION HAZARDS: This product is flammable and forms explosive mixtures with air. Vapors are heavier than air and will travel along surfaces to remote ignition sources and flash back. Closed containers may explode if exposed to extreme heat.

SPECIAL FIREFIGHTING INSTRUCTIONS: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing. Do not allow run-off from fire fighting to enter drains or water courses.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon and nitrogen, acrolein, ketones, and aldehydes.

EXPLOSION DATA (sensitivity to mechanical impact or static discharge): Flammable vapors may be ignited by static spark. Electrically bond and ground containers for product transfer.

6. ACCIDENTAL RELEASE MEASURES

Remove all sources of ignition. Ventilate area with explosion proof equipment. Wear appropriate protective clothing as described in Section 8. Contain and collect using inert absorbent materials and place in appropriate containers for disposal. Report releases as required by local, state and federal authorities.

7. HANDLING AND STORAGE

HANDLING: Avoid contact with the eyes, skin and clothing. Avoid breathing vapors. Wear protective clothing and equipment as described in Section 8. Use only with adequate ventilation. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep product away from heat, sparks, flames and all other sources of ignition. Do not permit smoking in use or storage areas. Use with non-sparking tools and explosion proof equipment. Electrically bond and ground containers for transfer. Do not cut, drill, grind or weld on or near containers, even empty containers. Empty containers retain product residues can be hazardous. Follow all MSDS precautions when handling empty containers.

STORAGE: Store in accordance with regulations for the storage of flammable liquids. Do not store above 49°C (120°F). Store in a dry, well ventilated area away from heat, direct sunlight and all sources of ignition. Store away from oxidizers and acids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES: Refer to Section 2.

ENGINEERING CONTROLS: Use with adequate local exhaust ventilation to maintain exposures below the occupational exposure limits. Use explosion proof equipment.



RESPIRATORY PROTECTION: If the exposure limits are exceeded a NIOSH approved respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

SKIN PROTECTION: Wear impervious gloves such as teflon.

EYE PROTECTION: Safety goggles and/or face shield should be worn where contact is possible. Do not wear contact lenses.

OTHER: Impervious clothing as needed to prevent contact. A safety shower and eye wash should be available in the immediate work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Water-white liquid with a ketone odor. The odor threshold for acetone is reported to be 62 ppm. The odor threshold for toluene is reported to be 1.6 ppm.

PHYSICAL STATE: Liquid
BOILING POINT: 56.5°C (133°F) (acetone)
VAPOR PRESSURE: 180 mm Hg @ 25°C (acetone)
VAPOR DENSITY: 3.3 (toluene)
EVAPORATION RATE: 11.6 (acetone) (n-butyl acetate=1)
SOLUBILITY IN WATER: Partially
BULK DENSITY: 6.80 lbs/gal
pH: NA
MELTING POINT: NA
OCTANOL/WATER COEFFICIENT: ND
VOC CONTENT: 341 g/liter

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal storage and handling conditions.

INCOMPATIBILITY: Strong acids and oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon and nitrogen, acrolein, ketones, and aldehydes.

HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL INFORMATION

HEALTH HAZARDS:

INGESTION: Ingestion may cause mucous membrane and gastrointestinal irritation and nervous system depression with symptoms of headache, dizziness, nausea, narcosis and unconsciousness. Aspiration into the lungs during ingestion or vomiting may cause serious lung damage which may be fatal.

INHALATION: Inhalation of vapors may cause mucous membrane and respiratory irritation and central nervous system depression with symptoms of headache, dizziness, nausea, vomiting, disorientation, stupor and unconscious. Severe overexposures may cause respiration depression and death.

EYE: Contact may cause irritation.

SKIN: Repeated or prolonged contact may cause irritation, drying and defatting. The liquid may be absorbed through the skin causing effects similar to those described under inhalation and ingestion.

SENSITIZATION: This product is not expected to cause sensitization.

CHRONIC/CARCINOGENICITY: Prolonged occupational overexposure may cause cardiac sensitization, effects on hearing and damage to the nervous system, blood system, liver and kidneys. Prolonged intentional toluene abuse may damage many organ systems including: central and peripheral nervous systems, vision, hearing, liver, kidneys, heart and blood. Such abuse has been associated with brain damage characterized by disturbances in gait, personality changes and loss of memory. Toluene has been found to cause adverse reproductive effects and/or birth defects in studies with laboratory animals. No ingredient in this product present at greater than 0.1% is listed as a carcinogen by NTP, IARC, or OSHA.

MUTAGENICITY: Acetone and toluene have tested positive for mutagenicity in some test systems.

STS Material Safety Data Sheet

Material: BP-40 Butyl Tape Primer

Item No.: BP-40

Created on 10/14/2009 12:56:00 PM

Page 3 of 5

¹ Hazard Ratings: least = 0 slight = 1 moderate = 2 high = 3 extreme = 4 Based upon NPCA guidelines



SYNERGISTIC PRODUCTS: None specifically known. Products containing chemicals that effect the same target organ systems would be expected to have synergistic effects; for example other solvent containing products.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Employees with pre-existing skin, liver and kidney disease may be at increased risk from exposure.

ACUTE TOXICITY VALUES:

Acetone: Oral Rat LD50 - 5800 mg/kg
Inhalation Rat LC50 - 50,100 mg/m³

Aliphatic Solvent Naphtha: Oral Rat LD50 - >25 mL/kg
Inhalation Rat LC50 - >14,000 ppm/4 hr
Skin Rabbit LD50 - > 5 mL/kg

Toluene: Oral Rat LD50 - 636 mg/kg
Inhalation Rat LC50 - 49 g/m³/4 hr
Skin Rabbit LD50 - 14100 uL/kg

12. ECOLOGICAL INFORMATION

No ecotoxicity data is available for this product at this time.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with local, state and federal environmental regulations.

14. TRANSPORT INFORMATION

DOT HAZARDOUS MATERIALS DESCRIPTION:

Proper Shipping Name: Paint Related Material (Contains Toluene, Acetone and Solvent Naphtha)

UN Number: UN1263

Hazard Class/Packing Group: 3, PG II

Labels Required: Flammable Liquid

Note: If >5000 pounds of this product in a single container, RQ requirements apply.

15. REGULATORY INFORMATION

CERCLA/SUPERFUND: This product has a Reportable Quantity (RQ) of 5000 lbs. based on the RQ for Toluene of 1000 lbs. Releases above the RQ must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA HAZARD CATEGORY (311/312): Acute Health, Chronic Health, Fire Hazard.

SARA 313 INFORMATION: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372):

Toluene 108-88-3 10-20%

EPA TSCA INVENTORY: All of the ingredients in this product are listed on the EPA TSCA Inventory.

CALIFORNIA PROPOSITION 65

This product contains the following chemicals known to the State of California to cause cancer:

Benzene <0.1%

This product contains the following chemicals known to the State of California to cause developmental toxicity (birth defects): Toluene 10-20%, Benzene <0.1%

This product contains the following chemicals known to the State of California to cause male reproductive toxicity: Benzene <0.1%

CANADA:

This product has been classified under the CPR and this MSDS discloses information elements required by the CPR.

CANADIAN WHMIS CLASSIFICATION: Class B Division 2 (Flammable Liquid); Class D Division 2 Subdivision A (Very Toxic Material Causing other Toxic Effects)



16. OTHER INFORMATION

NFPA RATING: Health = 2 Fire = 3 Reactivity = 0

HMIS RATING: Health = 2* Fire = 3 Reactivity = 0

NOTICE:

The information and recommendations contained herein are to the best of STS Coatings, Inc. knowledge and belief, accurate and reliable as of the date issued. STS Coatings, Inc. Does not warrant or guarantee their accuracy or reliability, and STS Coatings, Inc. shall not be liable for any loss or damage arising out of the use thereof.

The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. It is also the user's responsibility to make certain that it is relying up on the most recent, updated, information and recommendations available from STS Coatings, Inc.

The Environmental Information included as well as the Hazardous Material Identification System (HMIS) and National Fire Protection Association (NFPA) ratings, have been included by STS Coatings, Inc. in order to provide additional health and hazard classification information. The ratings recommended are based up on the criteria supplied by the developers of these rating systems, together with STS Coatings, Inc.'s interpretation of the available data.

For Other Product Information Contact:

STS Coatings, Inc.

347 Hwy 289

Comfort, TX 78013

PH. 830-995-5177

FAX 830-755-6494

info@stskoatings.com