

MATERIAL SAFETY DATA SHEET

ROOF GUARDIAN TECHNOLOGIES POLYESTER FABRIC

PRODUCT NAME: RGT POLYESTER FABRIC

PRODUCT CODE: PF-1000

MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: KST Coatings Manufacturing, Inc.

ADDRESS: 1499 ENTERPRISE PKWY

TWINSBURG, OH 44087

EMERGENCY PHONE: (800) 358-8810

DATE PRINTED: 02/08/02

INFORMATION PHONE: (330) 425-4717

NAME OF PREPARER: Paul D. Bauer

HAZARDOUS INGREDIENTS

There are no hazardous ingredients as defined in the "Code of Federal Regulations, Title 29, Part 1910.1200.

PHYSICAL HAZARDS

Polyester fabrics will melt at approximately 500°F. and will burn if exposed to flame. Decomposition products generated from molten polymer may be subject to auto ignition. Combustion products will be comprised of carbon, hydrogen, oxygen, and nitrogen. The exact composition will depend on the conditions of combustion.

HEALTH HAZARD INFORMATION

Exposure to polyester fabric would pose no significant health problems under normal conditions of handling and use.

EXPOSURE CONTROL METHODS

General ventilation is suggested. Recirculating systems should, whenever practical, be operated in the bypass mode to avoid concentrating air contaminants in the workspace.

Fire fighters should protect themselves from decomposition and combustion products that may include carbon monoxide and other toxic gases..

SAFE HANDLING PROCEDURES

Customary personal hygiene measures such as washing hands after working with such fabrics are recommended.

* **Federal Register – Page 53342, Paragraph 5:ii; Page 53343, Vol. 48, No. 228, 1983.**