

## PF-1000 Polyester Fabric

### Product Description

PF-1000 Polyester Fabric is an exceptionally strong material that offers an exceptional combination of high strength and excellent elongation. It easily accommodates the expansion and contraction from thermal forces induced by changing weather patterns and subsequent roof movement.

### Basic Use

PF-1000 Polyester Fabric is used as a reinforcement material with a variety of Roof Guardian Technologies Coatings. It readily conforms to most surfaces including standing seam metal roofs. PF-1000 Polyester Fabric is also ideal for use in a cap sheet system with Elastomeric or Emulsion coatings and for general roof repairs, flashings and parapet walls.

### Limitations

Install at temperatures over 50°F (10°C). Do not apply when rain is forecast.

### Surface Preparation

Surfaces must be clean, dry and free of oil and grease. Rusty surfaces must be cleaned and primed. Previous patching products must be removed, if possible.

### Application

To install as a capsheet system, roll out the fabric into wet base coat. Use a stiff broom and carefully "tamp down" on the fabric to aide in saturation. (Do not brush or push the fabric as wrinkling can occur). Overlap seams 4". Apply finish coat at the recommended rate of application.

### Maintenance

It is recommended that the coating installation be checked on a regular maintenance schedule. Small area touch ups can be made at any time following recommended application procedures.

### Technical Services

Technical advice on use of material for specific application and end use requirements is available from the manufacturer. Material Safety Data Sheet (MSDS) should be consulted for further information. This product is for industrial and professional use only.

### Packaging

Standard rolls available in 6" x 324' and 40" x 324'. Custom sizes can be purchased at additional charge.

### Warranty

This product is manufactured of good materials and by competent workmen. Seller's and manufacturer's only obligations shall be to replace such quantity of product as is proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising from the use or the inability to use the product. Before applying, Applicator shall determine the suitability of the product for his/her intended use; and user assumes all risk and liability.

ROOF GUARDIAN TECHNOLOGIES, INC. by STS  
347 Hwy 289, Comfort, TX 78013  
(210) 377-1055 phone (830)995-5705 fax  
[WWW.ROOFGUARDIANTECH.COM](http://WWW.ROOFGUARDIANTECH.COM)