

RG-13 Coal Tar Primer

Product Description

Roof Guardian Technologies (RGT) RG-13 Coal Tar Primer is a blend of refined coal tar pitch and aromatic solvents, designed to penetrate porous surfaces and bind chalky, dusty surfaces.

It enhances the adhesion of coal tar BUR, modified bitumen coal tar roofing systems, and protective coatings. It meets current VOC requirements, except in California. This is a non-asbestos product.

Basic Use

RG-13 creates a bondable surface over existing coal tar built up roofs.

Limitations

- Do not heat or thin.
- Do not use on 100% rubber or plastic substrates.
- Do not use on products containing asphalt.
- Do not apply on damp or wet surface.
- Do not use where this product would come in contact with potable water.
- Exterior use only

Technical Data

Vehicle Base	Coal Tar Pitch
Weight per Gallon (ASTM D6511)	9.3 lbs.
Solids by Weight (ASTM D6511)	65-70
Solids by Volume.....	53-58
Viscosity, seconds (Saybolt Furol).....	35-75
Dry Time.....	overnight
Sets to Touch	2 hours
Volatile Organic Compound (VOC) ...	450 Gr/L max
Flash Point (open cup).....	105°F Min.
Clean Up.....	OSHA approved aromatic solvent
Shelf Life	1 year
ASTM	D43

Surface Preparation

All surfaces must be cleaned by brooming, sweeping, or power washing to remove dust, dirt, debris, and loose gravel. Repair torn flashings,

parapet walls, blisters, open seams, and surface breaks.

Application

RG-13 Coal Tar Primer is ready to apply can be brushed or squeegeed. Cover surface completely. **Do not thin.**

Coverage

Apply in two coats, perpendicular to one another. Each coat should be applied at a rate of 1/4 to 2/3 gallons per square.

Clean Up

Immediately rinse/flush equipment and tools with an OSHA approved aromatic solvent after use. Exercise all flammable liquid precautions. Use a waterless hand cleaner on skin to remove.

Technical Services

Technical advice, for use of material in specific applications and end use requirements, is available from the manufacturer. Material Safety Data Sheet (MSDS) should be consulted for further information. This product is for industrial and professional use only.

Packaging

55 gallon drums (540 lbs)
5 gallon pails (48 lbs)

Warranty

This product is manufactured of good materials and by competent workmen. Seller's and manufacturer's only obligations shall be to replace such quantity of product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising from the use or the inability to use the product. Before using, user shall determine the suitability of the product for his/her intended use; and user assumes all risk and liability.

ROOF GUARDIAN TECHNOLOGIES, INC. by STS
347 Hwy 289, Comfort, TX 78013
(830)995-5177 phone (830)995-5705 fax
WWW.ROOFGUARDIANTECH.COM