

**RGT PRODUCT APPROXIMATE COVERAGE RATES**

Elastomeric Coatings – products needed depend on type of roof in place

|                |   |
|----------------|---|
| 15 Year System | 2.0 gal/100 sq.ft. RG-130 Gray Base<br>2.0 gal/100 sq.ft. RG-170 White Finish   |
| 10 Year System | 1.5 gal/100 sq.ft. RG-130 Gray Base<br>1.5 gal/100 sq.ft. RG-170 White Finish<br>1.5 gal/100 sq.ft. RG-530 SP Gray Base |
| 5 Year System  | 1.5 gal/100 sq.ft. RG-170 White Finish<br>0.5 gal/100 sq.ft. RG-530 SP Gray Base  |

Aluminum Coatings

|               |                                   |
|---------------|-----------------------------------|
| 5 Year System | 1.5 gal/100 sq.ft. RG-51 Aluminum |
|---------------|-----------------------------------|

Flashing Compound

|           |                          |
|-----------|--------------------------|
| Fasteners | 900 fasteners/1.0 gal    |
| Seams     | 1.0 gal/25 sq.ft. RG-110 |

Clear Skylight Coating

|                                  |
|----------------------------------|
| 1.0 gal/300 – 400 sq. ft. RG-190 |
|----------------------------------|

Primers

|                |                              |
|----------------|------------------------------|
| Black Asphalt  |                              |
| Non-porous     | 1 to 5 gal/100 sq.ft. RG-11  |
| Porous surface | 2 to 5 gal/100 sq. ft. RG-11 |

|              |                                 |
|--------------|---------------------------------|
| Bond-It Wash | 1.0 gal/400 – 500 sq.ft. RG-500 |
|--------------|---------------------------------|

|                |                            |
|----------------|----------------------------|
| BUR/MB Acrylic | 2.0 gal/100 sq. ft. RG-300 |
|----------------|----------------------------|

|          |                                |
|----------|--------------------------------|
| No Stain | .66 (2/3) gal/100 sq.ft. RG-12 |
|----------|--------------------------------|

|                 |                            |
|-----------------|----------------------------|
| Rust Inhibiting | 1.0 gal/250 sq. ft. RG-100 |
|-----------------|----------------------------|

No Slope Resurfacing Membrane

|                      |                          |
|----------------------|--------------------------|
| Modified Bitumen     | 2-4 gal/100 sq.ft. RG-15 |
| Gravel Surfaced Roof | 6-8 gal/100 sq.ft. RG-15 |

Black Asphalt Emulsion Coating

|                |                          |
|----------------|--------------------------|
| Porous surface | 3-4 gal/100 sq.ft. RG-21 |
| Non-porous     | 2-3 gal/100 sq.ft. RG-21 |
| Cold process   | 5-6 gal/100 sq.ft. RG-21 |