

RG-11 Black Asphalt Primer

Product Description

Roof Guardian Technologies (RGT) RG-11 Black Asphalt Primer is formulated with a select blend of oxidized asphalt and refined solvents to penetrate porous surfaces and bind chalky, dusty roof surfaces.

Basic Use

Ideal for use as a primer for RGT Asphalt Emulsion and Aluminum coatings. RG-11 Black Asphalt Primer saturates and binds dry or dusty roofing felts and scrim providing adhesion for protective coatings.

Limitations

- Do not heat or thin.
- Do not use on 100% rubber or plastic substrates.
- Do not use on products containing asphalt.
- Do not apply on damp or wet surface.
- Do not use where this product would come in contact with potable water.
- Exterior use only

Technical Data

Vehicle Base	Asphalt
Weight per gal ASTM D6511	7.3 lbs
Solids by Weight ASTM D6511	53% +/- 2%
Solids by Volume	52% +/- 2%
Viscosity, seconds (Saybolt Furol)	25 – 75
Dry Time – sets to touch	2 hours
VOC	450 gr/L
Flash Point – open cup	105°F Min. (37°C)
Shelf Life	1 year
Solvent	Mineral Spirits
Clean Up	Mineral Spirits

Surface Preparation

All surfaces must be cleaned by brooming, sweeping, or power washing to remove dust, dirt, debris, and loose gravel. Repair torn flashings, parapet walls, blisters, open seams, and surface breaks.

Application

RG-11 is ready to apply can be brushed or squeegeed. Cover surface completely. **Do not thin.**

Coverage

Apply in two coats, perpendicular to one another. Each coat should be applied at a rate of 1/4 to 2/3 gallons per square.

Clean Up

Immediately rinse/flush equipment and tools with an OSHA approved aromatic solvent after use. Exercise all flammable liquid precautions. Use a waterless hand cleaner on skin to remove.

Maintenance

It is recommended that the coating installation be checked on a regular maintenance schedule. Small area touch ups can be made at any time following recommended application procedures.

Technical Services

Technical advice, for use of material in specific applications and end use requirements, is available from the manufacturer. Material Safety Data Sheet (MSDS) should be consulted for further information. This product is for industrial and professional use only.

Packaging

- 55 gallon drums (208.2 liters) (452 lbs)
- 5 gallon pails (18.9 liters) (40 lbs)

Warranty

This product is manufactured of good materials and by competent workmen. Seller's and manufacturer's only obligations shall be to replace such quantity of product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising from the use or the inability to use the product. Before using, user shall determine the suitability of the product for his/her intended use; and user assumes all risk and liability.